

Polyconic projection. 1927 North American datum 10,000-foot grid based on Ohio coordinate system, north zone 1000-meter Universal Transverse Mercator grid ticks, zone 17, shown in blue

Red tint indicates area in which only landmark buildings are shown

Entire area lies within Congress Lands Land lines based on the First Principal Meridian

The difference between 1927 North American Datum and North American Datum of 1983 (NAD 83) for 7.5-minute intersections is given in USGS Bulletin 1875. The NAD 83 is shown by dashed corner ticks

U.S. Route State Route CONTOUR INTERVAL 5 FEET 2½° 44 MILS 1°55′ 34 MILS OHIO as IND MISTORICAL NATIONAL GEODETIC VERTICAL DATUM OF 1929 🔵 Interstate Route MAP ARCHIVES FEB 0 5 1992 BLUFFTON, OHIO QUADRANGLE LOCATION 40083-H8-TF-024 PHOTOINSPECTED 1988 1960 PHOTOREVISED 1972 DMA 4265 IV NW-SERIES V852 UTM GRID AND 1972 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS Revisions shown in purple compiled in cooperation with FOR SALE BY U.S. GEOLOGICAL SURVEY REC'D FILE COPY State of Ohio agencies from aerial photographs taken DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092 Map photoinspected 1988 No major culture or drainage changes observed 1972. This information not field checked A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST