


Mapped, edited, and published by the Geological Survey  
Control by USGS and USC&GS  
Topography by photogrammetric methods from aerial  
photographs taken 1960. Field checked 1961.  
Polyconic projection. 1927 North American datum. 10,000-foot grid  
based on Ohio coordinate system, north zone. 1000-meter Universal  
Transverse Mercator grid ticks, zone 17, shown in blue.  
Land lines within the Old Seven Ranges based on the Ohio River Base  
Land lines within the United States Military District based on the  
Base Line of the United States Military District  
Areas covered by dashed light-blue pattern are subject to  
controlled inundation to 916 feet by Dover Dam, 962 feet by  
Bolivar Dam and 941 feet by Atwood Lake  
Fine red dashed lines indicate selected fence and field lines where  
generally visible on aerial photographs. This information is unchecked

UTM GRID AND 1978 MAGNETIC NORTH  
DECLINATION AT CENTER OF SHEET  
Map photinspected 1988  
No major culture or drainage changes observed



The difference between 1927 North American Datum and North  
American Datum of 1983 (NAD 83) for 7.5-minute intersections  
is given in USGS Bulletin 1875. The NAD 83 is shown by  
dashed corner ticks  
Revisions shown in purple compiled in cooperation with  
State of Ohio agencies from aerial photographs taken  
1971 and 1976. Map edited 1978  
This information not field checked

ROAD CLASSIFICATION  
Heavy-duty ——— Light-duty ———  
Medium-duty ——— Unimproved dirt ———  
○ State Route  
MINERAL CITY, OHIO  
40081E3-TF024  
PHOTOINSPECTED 1988  
1961  
PHOTOREVISED 1971 AND 1978  
DMA 4765 III SE—SERIES V852

