



Mapped, edited, and published by the Geological Survey  
Control by USGS and USC&GS  
Topography by photogrammetric methods from aerial photographs taken 1957 and 1959-60. Field checked 1961  
Polyconic projection. 1927 North American datum  
10,000-foot grid based on Ohio coordinate system, south zone  
1000-meter Universal Transverse Mercator grid ticks, zone 16, shown in blue  
Red tint indicates areas in which only landmark buildings are shown  
Land lines based on the Great Miami River Base  
Areas covered by dashed light-blue pattern are subject to controlled inundation to 818 feet by Taylorsville Dam  
Fine red dashed lines indicate selected fence and field lines where generally visible on aerial photographs. This information is unchecked



CONTOUR INTERVAL 5 FEET  
DATUM IS MEAN SEA LEVEL

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS  
FOR SALE BY U.S. GEOLOGICAL SURVEY, WASHINGTON, D. C. 20242  
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ROAD CLASSIFICATION	
Heavy-duty	Light-duty
Medium-duty	Unimproved dirt
Interstate Route	U.S. Route
	State Route

QUADRANGLE LOCATION  
Revisions shown in purple compiled in cooperation with State of Ohio agencies from aerial photographs taken 1972. This information not field checked  
Purple tint indicates extension of urban areas

JUL 30 1973  
TROY, OHIO  
N4000-W8407.5/7.5  
1961  
PHOTOREVISED 1972  
AMS 4164 II SW—SERIES V852

3080