


Control by USC&GS, USGS, USED, and TVA
Topography by USGS and TVA from aerial
photographs by stereophotogrammetric methods
Field examination by Tennessee Valley Authority, 1947



SCALE 1:24 000
1 000 000 FEET
1 KILOMETER
Contour interval 20 feet
Occasional 10 foot contours shown by broken lines
Datum is mean sea level
THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON, D. C. 20242.
U. S. TENNESSEE VALLEY AUTHORITY, CHATTANOOGA OR KNOXVILLE, TENN.,
AND TENNESSEE DIVISION OF GEOLOGY, NASHVILLE, TENNESSEE
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

Polyconic projection. 1927 North American datum
10,000-foot grid based on Tennessee
rectangular coordinate system
1000-meter Universal Transverse Mercator grid ticks,
zone 16, shown in blue
ROUTES USUALLY TRAVELED
HARD, IMPERVIOUS SURFACES
OTHER SURFACE IMPROVEMENTS
(84) U. S. ROUTE (9) STATE ROUTE
MULBERRY, TENN.
80-NW
N3507.5-W8622.5/7.5
1947
AMS 3754 III NW-SERIES V841

U.S.G.S.
HISTORICAL FILE
TOPOGRAPHIC DIVISION

U.S.G.S.
FILE COPY
TOPOGRAPHIC DIVISION

1020
JAN 1 1956