



CONVERSION SCALES

Feet	Meters
15000	4500
14000	4000
13000	3500
12000	3000
11000	2500
10000	3000
9000	2500
8000	2000
7000	1500
6000	1000
5000	1500
4000	1000
3000	500
2000	500
1000	500
500	250
250	100
100	50
50	25
0	0

To convert feet to meters multiply by 3048  
To convert meters to feet multiply by 3.2808

Mapped, edited, and published by the Geological Survey  
Control by USGS, NOS/NOAA, and North Carolina Geodetic Survey  
Topography by photogrammetric methods from aerial photographs taken 1977. Field checked 1979. Map edited 1980  
Projection and 10,000-foot grid ticks: North Carolina coordinate system, (Lambert conformal conic)  
1000-meter Universal Transverse Mercator grid, zone 18  
1927 North American Datum  
To place on the predicted North American Datum 1983 move the projection lines 12 meters south and 26 meters west as shown by dashed corner ticks  
Short dashed blue lines indicate elliptical bay outlines visible on aerial photographs  
Fine red dashed lines indicate selected fence and field lines where generally visible on aerial photographs. This information is unchecked



CONTOUR INTERVAL 2 METERS  
NATIONAL GEODETIC VERTICAL DATUM OF 1929  
CONTROL ELEVATIONS SHOWN TO THE NEAREST 0.1 METER  
OTHER ELEVATIONS SHOWN TO THE NEAREST 0.5 METER

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS FOR SALE BY U.S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092  
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST



ROAD CLASSIFICATION

Primary highway, hard surface	Light-duty road, hard or improved surface
Secondary highway, hard surface	Unimproved road
Interstate Route	U.S. Route
	Slate Route

RIVERMONT, N. C.  
NE4 DEEP RUN 15' QUADRANGLE  
N3507.5-W7730/7.5  
1980  
DMA 5454 II NE-SERIES V842

USGS  
Historical File  
National Mapping Div.  
2050  
MAY 20 1981