



Mapped, edited, and published by the Geological Survey

Control by USGS and NOS/NOAA

Topography by photogrammetric methods from aerial photographs taken 1970. Field checked 1971

Selected hydrographic data compiled from NOS/NOAA Chart 18535 (1970) This information is not intended for navigational purposes

Polyconic projection. 1927 North American Datum 10,000-foot grid based on Oregon coordinate system, north zone and Washington coordinate system, south zone 1000-meter Universal Transverse Mercator grid ticks, zone 10, shown in blue

The difference between 1927 North American Datum and North American Datum of 1983 (NAD 83) for 7.5 minute intersections is given in USGS Bulletin 1875. The NAD 83 is shown by dashed corner ticks

Fine red dashed lines indicate selected fence lines



UTM GRID AND 1971 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET



CONTOUR INTERVAL 20 FEET
NATIONAL GEODETIC DATUM OF 1929
DEPTH CURVES AND SOUNDINGS IN FEET—DATUM IS NORMAL POOL ELEVATION 265 FEET



QUADRANGLE LOCATION

ROAD CLASSIFICATION

- Primary highway, hard surface
- Secondary highway, hard surface
- Light duty road, hard or improved surface
- Unimproved road
- Interstate Route
- U.S. Route
- State Route

QUINTON, OREG.-WASH.
45120-F5-TF-024

1971

DMA 1875 II NE-SERIES V892

