



Maped by the Army Map Service
Edited and published by the Geological Survey
Revised by the Geological Survey in cooperation with New York
Department of Transportation

Control by USGS, USC&GS and Nassau County
Planimetry by photogrammetric methods from aerial photographs
taken 1941. Topography by planetable surveys 1943. Revised 1967
Selected hydrographic data compiled from USC&GS Charts 222 (1963)
and 224 (1966). This information is not intended for navigational purposes

Polyconic projection. 1927 North American datum
10,000-foot grids based on New York coordinate system, Long Island zone
and Connecticut coordinate system
1000-metre Universal Transverse Mercator grid ticks, zone 18,
shown in blue

Red tint indicates areas in which only landmark buildings are shown

SCALE 1:24 000

CONTOUR INTERVAL 20 FEET
NATIONAL GEODETIC VERTICAL DATUM OF 1929
DEPTH CURVES AND SOUNDINGS IN FEET—DATUM IS MEAN LOW WATER
SHORELINE SHOWN REPRESENTS THE APPROXIMATE LINE OF MEAN HIGH WATER
THE MEAN RANGE OF TIDE IS APPROXIMATELY 7.4 FEET

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ROAD CLASSIFICATION

Heavy-duty .Light-duty
Medium-duty Unimproved dirt

UTM GRID AND 1967 MAGNETIC NORTH
DECLINATION AT CENTER OF SHEET

QUADRANGLE LOCATION

BAYVILLE, N.Y.—CONN.

N4052.5—W7330.7.5

1967

AMS 6265 I NE—SERIES V821

APR 12 1971

5200