



V502, EDITION 3
 Prepared by the U.S. Army Topographic Command (ASGE), Washington, D.C. Compiled in 1955 by photogrammetric methods and from United States quadrangles, 1:24,000 and 1:62,500, 1915-52. Planimetry revised from photographs taken 1953. Photographic field annotated 1953. Geodetic control established by government agencies as shown on the U.S. Geological Survey 1970. Geodetic control diagram is showing 1:250,000-scale Geodetic Control Diagram.

UT 280
 TF
 0-607-55921-7
 9780601552171

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES

LOS ANGELES
 OMAHA
 GALVESTON
 Laramie
 Grand Coulee
 Sun Valley

ROADS

Primary, all-weather, hard surface
 Secondary, all-weather, hard surface
 Light-duty, all-weather, hard or improved surface
 Fair or dry weather, unimproved surface
 Trail
 Interchange

RAILROADS

Standard gauge
 Narrow gauge
 International
 State
 County
 Park or reservation

BOUNDARIES

Landplane airport
 Landing area
 Seaplane airport
 Seaplane anchorage
 Woods brushwood

Landmarks: School; Church; Other

Mine
 Spot elevation in feet
 Marsh or swamp
 Intermittent or dry stream
 Power line

Scale 1:250,000

0 5 10 15 20 25 30 Statute Miles
 0 5 10 15 20 25 30 Kilometers
 0 5 10 15 Nautical Miles

**CONTOUR INTERVAL 200 FEET
 WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS
 TRANSVERSE MERCATOR PROJECTION**

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 12

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 16°16' (200 MILES) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 14° (200 MILES) WESTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR WASHINGTON, D.C. 20242

LOCATION DIAGRAM

NEVADA	UTAH	WYOMING	NEBRASKA	KANSAS	MISSOURI	ILLINOIS	INDIANA	MICHIGAN	OHIO	PENNSYLVANIA	MARYLAND	DELAWARE	NEW JERSEY	NEW YORK	CONNECTICUT	MASSACHUSETTS	VERMONT	N.H.	ME.
NK 11-8	NK 11-9	NK 11-10	NK 11-11	NK 11-12	NK 12-1	NK 12-2	NK 12-3	NK 12-4	NK 12-5	NK 12-6	NK 12-7	NK 12-8	NK 12-9	NK 12-10	NK 12-11	NK 12-12	NK 12-13	NK 12-14	NK 12-15

SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

GRID ZONE DESIGNATION

12N
 100 000 W. SQUARE IDENTIFICATION

TO OBTAIN A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS

SAMPLE POINT: CLOSURE

1. Read letters identifying 100,000 meter square in which the point lies.
 2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure following the line within the top or bottom margin, or on the line itself.
 3. Locate first HORIZONTAL grid line below point and read LARGE figure following the line within the left or right margin, or on the line itself.
 4. Estimate meters from grid line to point. Example: South from grid line to point: 440,000
 5. If spacing beyond 10' in any direction, prefix Grid Zone Designation, as: 12T07666

STOCK NO. V502XNK1210*03