



Prepared by the U.S. Army Topographic Command (BEAM), Washington, D.C. Compiled in 1953 by photogrammetric methods and from United States quadrangles 1:24,000 and 1:62,500, 1930-51. Planimetry revised from aerial photographs taken 1952. Photographs field annotated 1952. Revised in 1971 by the U.S. Geological Survey from aerial photographs taken 1970.

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES

- Over 500,000
- 100,000 to 500,000
- 25,000 to 100,000
- 5,000 to 25,000
- 1,000 to 5,000
- Less than 1,000

RAILROADS

- Standard gauge
- Narrow gauge
- Interchange
- Sun Valley

ROADS

- Primary, all-weather, hard surface
- Secondary, all-weather, hard surface
- Light-duty, all-weather, hard or improved surface
- Fair or dry weather, unimproved surface
- Trail

BOUNDARIES

- International
- State
- County
- Park or reservation

Other Features

- Landplane airport
- Landing area
- Seaplane airport
- Seaplane anchorage
- Woods/bushwood
- Spot elevation in feet
- Marsh or swamp
- Intermittent or dry stream
- Power line

Scale 1:250,000

0 5 10 15 20 25 30 Statute Miles

0 5 10 15 20 25 30 Kilometers

0 5 10 15 20 25 30 Nautical Miles

CONTOUR INTERVAL 100 FEET

WITH SUPPLEMENTARY CONTOURS AT 50 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 14

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 11° (200 MILES) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 9°45' (170 MILES) EASTERLY FOR THE CENTER OF THE EAST EDGE.

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092

LOCATION DIAGRAM

Map showing the location of New Rockford, North Dakota, within the United States and surrounding countries (Canada, Mexico).

SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

GRID ZONE DESIGNATION

14T

100,000 M. SQUARE IDENTIFICATION

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS

SAMPLE POINT: BARLOW

1. Read letters identifying 100,000 meter square in which the point lies.

2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.

3. Estimate tenths from grid line to point.

4. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.

5. Estimate hundredths from grid line to point.

SAMPLE REFERENCE:

If reporting beyond 18° in any direction, prefix Grid Zone Designation, as:

14THN868