



Control by USC&GS, USGS, USED, and TVA
Topography by USGS and TVA from aerial
photographs by stereophotogrammetric methods
Field examination by Tennessee Valley Authority, 1945

TRUE NORTH
MAGNETIC NORTH
APPROXIMATE MEAN
DECLINATION, 1946

Scale 24,000
1 inch = 2 miles
1 centimeter = 2 kilometers

Contour interval 20 feet
Occasional 10 foot contours shown by broken lines
Datum is mean sea level

FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C.
U. S. TENNESSEE VALLEY AUTHORITY, CHATTANOOGA OR KNOXVILLE, TENN.
AND TENNESSEE DIVISION OF GEOLOGY, NASHVILLE, TENN.
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USGS
Historical File
Topographic Division

USGS
FILE COPY
TOPOGRAPHIC DIVISION

HISTORICAL

Reproduced 1960-USCOMM-CGS-DCIR 1866
TENN. 2,110,000 FEET
R. 9 E. R. 10 E.
1625000m E.
85° 37' 30"

Polyconic projection, 1927 North American datum
10,000 foot grid based on Alabama (East) and
Tennessee rectangular coordinate systems
1000-meter Universal Transverse Mercator
grid ticks, Zone 16, shown in blue

ROUTES USUALLY TRAVELED
HARD, IMPERVIOUS SURFACES
OTHER SURFACE IMPROVEMENTS
U. S. ROUTE STATE ROUTE

BRIDGEPORT, ALA.-TENN.
101-NW
N3452.5-W8537.5/7.5
1945