



Mapped, edited, and published by the Geological Survey  
Control by USGS, NOS/NOAA, and Alabama Geodetic Survey  
Culture and drainage in part compiled from aerial photographs  
taken 1954. Topography by planetable surveys 1956  
Selected hydrographic data compiled from NOS chart 1266 (1952)  
This information is not intended for navigational purposes  
Polyconic projection. 10,000-foot grid ticks based on  
Alabama coordinate system, west zone  
1000-meter Universal Transverse Mercator grid ticks,  
zone 16, shown in blue  
1927 North American Datum  
To place on the predicted North American Datum 1983  
move the projection lines 18 meters south and  
1 meter west as shown by dashed corner ticks  
Revisions shown in purple and woodland compiled from  
aerial photographs taken 1981 and other sources. This  
information not field checked. Map edited 1985



CONTOUR INTERVAL 10 FEET  
SUPPLEMENTARY CONTOUR INTERVAL 5 FEET  
NATIONAL GEODETIC DATUM OF 1929  
DEPTH CURVES AND SOUNDINGS IN FEET—DATUM IS MEAN LOWER LOW WATER  
THE RELATIONSHIP BETWEEN THE TWO DATUMS IS VARIABLE  
SHORELINE SHOWN REPRESENTS THE APPROXIMATE LINE OF MEAN HIGH WATER  
THE MEAN RANGE OF TIDE IS APPROXIMATELY 1.4 FEET  
THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS  
FOR SALE BY U. S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092  
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST



USGS NMD HISTORICAL MAP  
MAR 3 1 1986  
REC'D FILE COPY

ROAD CLASSIFICATION

Heavy-duty	Light-duty
Medium-duty	Unimproved dirt
U. S. Route	State Route

POINT CLEAR, ALA.  
30087-D8-TF-024  
1956  
PHOTOREVISED 1985  
DMA 3444 IV NW—SERIES 9844