





CONVERSION SCALES

Feet	Meters
1	0.3048
2	0.6096
3	0.9144
4	1.2192
5	1.5240
6	1.8288
7	2.1336
8	2.4384
9	2.7432
10	3.0480

To convert feet to meters multiply by 0.3048  
To convert meters to feet multiply by 3.2808



Produced by the United States Geological Survey and the National Ocean Service  
Control by USGS and NOS/NOAA  
Orthophotomaps prepared from aerial photographs taken January 10, 1976. Compiled by photogrammetric methods from aerial photographs taken January 1975. Field checked 1976. Map edited 1982.  
Bathymetry compiled by the National Ocean Service from tide-coordinated hydrographic surveys.  
This information is not intended for navigational purposes. Mean low water (dotted) line and mean high water (solid) line compiled by NOS from tide-coordinated aerial photographs. Apparent shoreline (outer edge of vegetation) shown by photomappers.  
Projection and 10,000-foot grid ticks: Florida coordinate system, north zone (Lambert conformal conic).  
1000-meter Universal Transverse Mercator grid ticks, zone 16 1927 North American Datum (NAD 27).  
North American Datum of 1983 (NAD 83) is shown by dashed corner ticks. The value of the shift between NAD 27 and NAD 83 for 7.5-minute intersections are given in USGS Bulletin 1875.  
There may be private inholdings within the boundaries of the National or State reservations shown on this map. Photosinspected from 1990 source; no major culture or drainage changes observed. Names verified 1992.



SCALE 1:24 000

1 000 0 1000 2000 3000 4000 5000 6000 7000 8000 9000 10000

1 000 0 1000 2000 3000 4000 5000 6000 7000 8000 9000 10000

1 000 0 1000 2000 3000 4000 5000 6000 7000 8000 9000 10000

CONTOUR INTERVAL 2 METERS  
SUPPLEMENTARY CONTOUR INTERVAL 1 METER  
DASHED SUPPLEMENTARY CONTOURS ARE APPROXIMATE  
NATIONAL GEODETIC VERTICAL DATUM OF 1929  
CONTROL ELEVATIONS SHOWN TO THE NEAREST 0.1 METER  
OTHER ELEVATIONS SHOWN TO THE NEAREST 0.3 METER  
BATHYMETRIC CONTOUR INTERVAL 1 METER WITH SUPPLEMENTARY 0.5 METER CONTOURS - DATUM IS MEAN LOWER LOW WATER  
THE RELATIONSHIP BETWEEN THE TWO DATUMS IS VARIABLE  
THE MEAN RANGE OF TIDE IS APPROXIMATELY 0.4 METER

BASE MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS  
BATHYMETRIC SURVEY DATA COMPLIES WITH INTERNATIONAL HYDROGRAPHIC ORGANIZATION (IHO) SPECIAL PUBLICATION 41 ACCURACY STANDARDS  
AND/OR STANDARDS USED AT THE DATE OF THE SURVEY

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092  
AND NATIONAL OCEAN SERVICE, ROCKVILLE, MARYLAND 20852  
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

NATIONAL OCEAN SURVEY HYDROGRAPHIC SURVEY INDEX

Survey Number	Survey Date	Survey Scale	Survey Line Spacing (Naut. Miles)
H-1265a	1875	1:20,000	10-30
H-6785	1942-43	1:40,000	10-30
H-6786	1942-43	1:20,000	02-13

ROAD CLASSIFICATION

Primary highway, hard surface — Light-duty road, hard or improved surface  
Secondary highway, hard surface — Unimproved road  
Trails —  
Interstate Route — U. S. Route — State Route  
County Route

CAPE SAN BLAS, FLA.  
29085-F3-TB-024  
1982  
MINOR REVISION 1992  
DMA 3943 II NE-SERIES V8470

