



Mapped by U.S. Coast and Geodetic Survey
Edited and published by the Geological Survey
Control by USC&GS (C), Florida Geodetic Survey (F) and USED (E)
Culture and drainage in part compiled from
aerial photographs taken 1942 and 1945. Field check 1947
Topography by Florida Geodetic Survey 1938 and 1939
revised and supplemented by plane-table methods, USC&GS 1945-1946
Polyconic projection. 1927 North American datum
10,000-foot grid based on Florida coordinate system,
east zone
Red tint indicates area in which only
landmark buildings are shown
No distinction is made between dwellings, barns,
commercial and industrial buildings

TRUE NORTH
MAGNETIC NORTH
APPROXIMATE MEAN
DECLINATION, 1947

SCALE 1:24000
1 0 1000 2000 3000 4000 5000 6000 7000 FEET
1 5 0 1 KILOMETER
CONTOUR INTERVAL 5 FEET
DATUM IS MEAN SEA LEVEL
SHORELINE SHOWN REPRESENTS THE APPROXIMATE LINE OF MEAN HIGH WATER
THE AVERAGE RANGE OF TIDE IS APPROXIMATELY 2 FEET
THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C.
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USCS
Historical File
Topographic Division

U.S.G.S.
FILE COPY
Inspection and Editing

ROAD CLASSIFICATION
HARD-SURFACE ALL WEATHER ROADS DRY WEATHER ROADS
Heavy-duty 1 LANE 1 LANE Improved dirt
Medium-duty 1 LANE 1 LANE Unimproved dirt
Loose-surface, graded, or narrow hard-surface
U. S. Route State Route

NORTH MIAMI, FLA.
N2552.5-W8007.5/7.5

EDITION OF 1950