



Produced by the United States Geological Survey  
Compiled by photogrammetric methods from imagery dated 1963. Field checked 1964  
North American Datum of 1927 (NAD 27). Projection and 10 000-foot ticks: Minnesota coordinate system, south zone (Lambert conformal conic)  
Blue 1000-meter Universal Transverse Mercator ticks, zone 15  
North American Datum of 1983 (NAD 83) is shown by dashed corner ticks. The values of the shift between NAD 27 and NAD 83 for 7.5-minute intersections are obtainable from National Geodetic Survey NADCON software  
Area covered by dashed light-blue pattern is subject to controlled inundation



CONTOUR INTERVAL 10 FEET  
NATIONAL GEODETIC VERTICAL DATUM OF 1929

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS  
FOR SALE BY U.S. GEOLOGICAL SURVEY  
DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092  
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST



ROAD CLASSIFICATION

Primary highway, hard surface	Light-duty road, hard or improved surface
Secondary highway, hard surface	Unimproved road
Interstate Route	U. S. Route
	Slate Route

Revisions shown in purple compiled in cooperation with State of Minnesota agencies from imagery dated 1991-92 and other sources. Map edited 1994  
Information shown in purple may not meet USGS content standards and may conflict with previously mapped contours

NEW ULM, MINN.  
44094-C4-TF-024  
1992  
DMA 7172 IV SW-SERIES V872

