


Produced by the United States Geological Survey in cooperation with the Louisiana Department of Transportation and Development. Topography compiled 1953. Planimetry derived from imagery taken 1998 and other sources. Public Land Survey System and survey control current as of 1991. North American Datum of 1983 (NAD 83). Projection and 1 000-meter grid: Universal Transverse Mercator, zone 15 10 000-foot ticks: Louisiana Coordinate System of 1983 (south zone) North American Datum of 1927 (NAD 27) is shown by dashed corner ticks. The values of the shift between NAD 83 and NAD 27 for 7.5-minute intersections are obtainable from National Geodetic Survey NADCON software. This quadrangle covers a subsidence area. Landmark buildings verified 1991.



CONTOUR INTERVAL 5 FEET NATIONAL GEODETIC VERTICAL DATUM OF 1929 TO CONVERT FROM FEET TO METERS, MULTIPLY BY 0.3048

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS FOR SALE BY U.S. GEOLOGICAL SURVEY, P.O. BOX 25286, DENVER, COLORADO 80225 AND LOUISIANA DEPARTMENT OF TRANSPORTATION AND DEVELOPMENT, BATON ROUGE, LOUISIANA 70804 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

QUADRANGLE LOCATION table with 8 numbered cells corresponding to map grid cells.

ADJOINING 7.5' QUADRANGLE NAMES

ROAD CLASSIFICATION legend: Primary highway, Secondary highway, Interstate Route, U.S. Route, State Route, Light-duty road, hard or improved surface, Unimproved road.

RECEIVED stamp: AUG 31 2000, LOBDELL, LA 1998, NIMA 7744 IV NE-SERIES V885

