


Mapped and edited by Tennessee Valley Authority
Published by the Geological Survey
Control by USC&GS, USGS, USED, and TVA
Topography by USGS and TVA by multiplex methods from aerial
photographs taken 1948. Field examination by TVA, 1950
Polyconic projection. 1927 North American datum
10,000-foot grid based on Mississippi (East) and
Alabama (West) rectangular coordinate systems
1000-meter Universal Transverse Mercator grid ticks,
zone 16, shown in purple
Grid declination 0°40' 12" West
Revisions in purple compiled by TVA, December 1967 from
April 1967 photography without field examination
No larger scale topographic maps available from TVA

TRUE NORTH
MAGNETIC NORTH
APPROXIMATE MEAN
DECLINATION 1950
1969



SCALE 1:24,000
CONTOUR INTERVAL 20 FEET
DASHED LINES REPRESENT HALF-INTERVAL CONTOURS
DATUM IS MEAN SEA LEVEL
THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C. 20242
AND BY U. S. TENNESSEE VALLEY AUTHORITY, CHATTANOOGA OR KNOXVILLE, TENN.
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USGS
Historical File
Topographic Division
LEGEND
Fence and field line
Stream
Pond and dam
Woodland (formerly clearing)
Clearing (formerly woodland)
General deletion
Foot trail
Mine or quarry
ROAD CLASSIFICATION
In developed areas, only through roads are classified
HARD-SURFACE ALL WEATHER ROADS
Heavy-duty
Medium-duty
Loose-surface, graded, or narrow hard-surface
DRY WEATHER ROADS
Improved dirt
Unimproved dirt
U. S. Route
State Route

U.S.G.S. BELMONT, MISS.-ALA.
N3430-W8807.5/7.5
1950
JUL 27 1971
26-SW
AMS 3353 II SW SERIES V693