


Mapped, edited, and published by the Geological Survey
Control by USGS and NOS/NOAA
Topography by photogrammetric methods from aerial photographs
taken 1951. Field checked 1953. Revised from aerial photographs
taken 1975. Field checked 1975. Map edited 1978
Polyconic projection. 1927 North American datum
10,000-foot grid ticks based on Kentucky coordinate system, south zone
1000-meter Universal Transverse Mercator grid, zone 16
Fine red dashed lines indicate selected fence and field lines where
generally visible on aerial photographs. This information is unchecked
Lake Cumberland Subject to controlled inundation to 760 feet
Underwater contours in Lake Cumberland from USCE charts dated 1943



CONTOUR INTERVAL 20 FEET
NATIONAL GEODETIC VERTICAL DATUM OF 1929

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092,
KENTUCKY GEOLOGICAL SURVEY, LEXINGTON, KENTUCKY 40506,
AND KENTUCKY DEPARTMENT OF COMMERCE, FRANKFORT, KENTUCKY 40601
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST



MAP AND AIR PHOTO
LIBRARY

FEB 21 1979

University of Wisconsin
Madison

ROAD CLASSIFICATION
Primary highway, hard surface ——— Light-duty road, hard or improved surface ———
Secondary highway, hard surface ——— Unimproved road ———
Interstate Route ——— U. S. Route ——— State Route ———

MILL SPRINGS, KY.
NE 1/4 MONTICELLO 15' QUADRANGLE
N3652.5-W8445.7.5

1978

AMS 4057 IV NE—SERIES V853