



Produced by the U. S. Geological Survey
Compiled by photogrammetric methods from imagery dated 1960
Field checked 1961
Photomapped using imagery dated 1992, no major culture or drainage changes observed. Boundaries and names revised 1995
North American Datum of 1927 (NAD 27). Projection and 10 000-foot ticks: Ohio coordinate system, south zone (Lambert conformal conic)
Blue 1000-meter Universal Transverse Mercator grid ticks, zone 17
North American Datum of 1983 (NAD 83) is shown by dashed corner ticks. The values of the shift between NAD 27 and NAD 83 for 7.5-minute intersections are obtainable from National Geodetic Survey NADCON software
There may be private inholdings within the boundaries of the National or State reservations shown on this map
Land lines based on the Ohio River Base. Dotted land lines established by private subdivision of the Ohio Company Purchase

UTM GRID AND 1995 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

SCALE 1:24 000
CONTOUR INTERVAL 20 FEET
DOTTED LINES REPRESENT 10-FOOT CONTOURS
NATIONAL GEODETIC DATUM OF 1929

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U.S. GEOLOGICAL SURVEY
DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

U.S. GEOLOGICAL SURVEY
AUG 4 1995
REC'D FILE COPY



ROAD CLASSIFICATION
Primary highway, hard surface
Secondary highway, hard surface
Light-duty road, hard or improved surface
Unimproved road
Interstate Route
U. S. Route
State Route

LOGAN, OH
39082-E4-TF-024
1992

DMA 4563 III SW-SERIES V852

