



LEGEND

POPULATED PLACES

- Over 500,000
- 100,000 to 500,000
- 25,000 to 100,000
- 5,000 to 25,000
- 1,000 to 5,000
- Less than 1,000

ROADS

- Primary, all-weather, hard surface
- Secondary, all-weather, hard surface
- Light-duty, all-weather, hard or improved surface
- Fair or dry weather, unimproved surface
- Trail
- Interchange
- Route markers: Interstate, U.S., State

RAILROADS

- Normal gauge
- Narrow gauge
- Landline airport
- Landing area
- Seaplane airport
- Seaplane anchorage
- Woods brushwood

BOUNDARIES

- International
- State
- County
- Park or reservation

Other symbols:

- Landmark: School, Church, Other
- Spot elevation in feet
- Fair or dry weather, unimproved surface
- Intermittent or dry stream
- Power line

Scale 1:250,000

0 5 10 15 20 25 30 Kilometers

0 5 10 15 20 25 30 Nautical Miles

CONTOUR INTERVAL 100 FEET

DOTTED LINES REPRESENT 50-FOOT CONTOURS

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 17

1978 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 3° 50' MILLS WESTERLY FOR THE CENTER OF THE WEST EDGE TO 4° 00' MILLS WESTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092

LOCATION DIAGRAM

Grid showing the location of Marion, Ohio, within the Eastern United States.

SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

TOWNSHIP OR RANGE LINE

LAND GRANT BOUNDARY

USGS Historical File Topographic Division

JAN 17 1980

MARION, OHIO

8500

1966 REVISED 1978