



U. S. G. S.
FILE COPY
Inspection and Editing.

Control by USCGS, USGS, and TVA.
Topography by Geological Survey from aerial
photographs by stereophotogrammetric methods.
Field examination by Tennessee Valley Authority, 1940
Maps distributed by the Geological Survey

Construction of Fort Loudoun Dam will raise the
Tennessee River and tributaries in the west portion
of this area. Proposed pool elevation, 812 feet.

Scale: 24000
1 inch = 2 miles
1:24000
0 1 2 Miles
0 1 2 Kilometers
10000 Feet

Contour interval 20 feet with 10 foot contours shown by broken line
Datum is mean sea level

Printed by the Geological Survey
USGS
HISTORICAL FILE
TOPOGRAPHIC DIVISION

Polynomial projection, 1927 North American datum
10,000 foot grid based on Tennessee rectangular
coordinate system

ROUTES USUALLY TRAVELED
HARD IMPROVED SURFACES
OTHER SURFACE IMPROVEMENTS
1940

U. S. ROUTE
STATE ROUTE

U. S. G. S.
FILE COPY
Inspection and Editing.

SHOOKS GAP, TENN.
147-NE
Edition of 1940
reprinted 1947
N 3552.5-W 8345/7.5

OCT 27 1947

2185