

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

UNITED STATES
DEPARTMENT OF THE ARMY
CORPS OF ENGINEERS

WARRENTON QUADRANGLE
OREGON - WASHINGTON
7.5 MINUTE SERIES (TOPOGRAPHIC - BATHYMETRIC)





CONVERSION
SCALES

Feet Meters



Feet Meters



Mapped by the Defense Mapping Agency and the National Ocean Service
Published for civil use by the Geological Survey
Control by NOS/NOAA, USCE and Pacific Power and Light Company
Topography from aerial photographs by multiplex methods
Aerial photographs taken 1943. Field checked 1953
Bathymetry compiled by the National Ocean Service from tide-coordinated hydrographic surveys. This information is not intended for navigational purposes
Mean low water (dotted) line and mean high water (heavy solid) line compiled by NOS from tide-coordinated aerial photographs. Apparent shoreline (outer edge of vegetation) shown by light solid line
Polyconic projection. 1927 North American Datum
10,000-foot grid based on Oregon coordinate system, north zone and Washington coordinate system, south zone
1000-meter Universal Transverse Mercator grid ticks, zone 10, shown in blue
To place on the predicted North American Datum 1983, move the projection lines 24 meters north and 97 meters east as shown by dashed corner ticks
There may be private inholdings within the boundaries of the National or State reservations shown on this map
Revisions shown in purple compiled by the Geological Survey from aerial photographs taken 1981 and other sources
This information not field checked. Map edited 1984

HYDROGRAPHIC SURVEY INFORMATION			
SURVEY NUMBER	SURVEY DATE	SURVEY SCALE	SURVEY LINE SPACING (NAUT. MILES)
H-8421	1935	1:10,000	01-05
H-8417	1958	1:20,000	03-35
H-8421	1958	1:10,000	01-17
H-8422	1958	1:10,000	01-17
NOS CHART 18521	MARCH 27, 1982	1:40,000	

SCALE 1:24,000
1 1000 0 1000 2000 3000 4000 5000 6000 7000 FEET
1 1 2 3 4 5 6 7 8 9 10 KILOMETER
CONTOUR INTERVAL 50 FEET
DASHED LINES REPRESENT 25 FOOT CONTOURS
NATIONAL GEODETIC VERTICAL DATUM OF 1929
BATHYMETRIC CONTOUR INTERVAL 2 METERS WITH SUPPLEMENTARY 1 METER CONTOURS - DATUM IS MEAN LOWER LOW WATER
THE RELATIONSHIP BETWEEN THE TWO DATUMS IS VARIABLE
THE MEAN RANGE OF TIDE IS APPROXIMATELY 2.4 METERS
BASE MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
BATHYMETRIC SURVEY DATA COMPLETES WITH INTERNATIONAL HYDROGRAPHIC ORGANIZATION (IHO) SPECIAL PUBLICATION 44 ACCURACY STANDARDS AND/OR STANDARDS USED AT THE DATE OF THE SURVEY
FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092
AND NATIONAL OCEAN SERVICE, ROCKVILLE, MARYLAND 20852
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ROAD CLASSIFICATION
Heavy-duty 4 LANE 6 LANE Light-duty 4 LANE 6 LANE
Medium duty 4 LANE 6 LANE Unimproved dirt =====
U. S. Route ○ State Route ○
QUADRANGLE LOCATION
WARRENTON, OREG.-WASH.
46123-B8-TB-024
1953
PHOTOREVISED 1984
BATHYMETRY ADDED 1984
DMA 1276 III NW - SERIES V892
UTM GRID AND 1984 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET
0°41' 12 MILS
20°4' 364 MILS
JAN 1996
REC'D FILE COPY