




V502, EDITION 3

Prepared by the U.S. Army Topographic Command (ASX), Washington, D.C. Compiled in 1955 by photogrammetric methods and from United States quadrangles, 1:24,000, 1:125,000, 1:900,000. Planimetry revised from aerial photographs taken 1953. Photographs field annotated 1954. Revised by the U.S. Geological Survey 1970.

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES

Over 500,000
100,000 to 500,000
25,000 to 100,000
5,000 to 25,000
1,000 to 5,000
Less than 1,000

ROADS

Primary, all-weather, hard surface
Secondary, all-weather, hard surface
Light-duty, all-weather, hard or improved surface
Fair or dry weather, unimproved surface
Trail
Grand Coulee
Sun Valley

RAILROADS

Standard gauge
Narrow gauge
Interchange
Route markers: Interstate, U.S., State

BOUNDARIES

International
State
County
Park or reservation

Landmarks: School; Church; Other

Other features:

Landplane airport
Landing area
Seaplane airport
Seaplane anchorage
Woods/bushwood
Spot elevation in feet
Marsh or swamp
Intermittent or dry stream
Power line

Scale 1:250,000

0 5 10 15 20 Statute Miles

0 5 10 15 20 25 30 Kilometers

0 5 10 15 20 25 30 Nautical Miles

CONTOUR INTERVAL 200 FEET

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 12

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 1° 00' (280 MILES) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 15° 15' (280 MILES) WESTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR WASHINGTON, D.C. 20242

LOCATION DIAGRAM

116° 115° 114° 113° 112° 111° 110° 109° 108° 107° 106°

38° 37° 36° 35° 34° 33° 32° 31° 30° 29° 28° 27° 26° 25° 24° 23° 22° 21° 20° 19° 18° 17° 16° 15° 14° 13° 12° 11° 10° 9° 8° 7° 6° 5° 4° 3° 2° 1°

SECTIONIZED TOWNSHIP

6 5 4 3 2 1
7 8 9 10 11 12
13 14 15 16 17 18
19 20 21 22 23 24
25 26 27 28 29 30
31 32 33 34 35 36

GRID ZONE DESIGNATION

12T

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS

1 Read letters identifying 100,000 meter square in which the point lies.
2 Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.
3 Estimate tenths from grid line to point.
4 Locate first HORIZONTAL grid line below point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.
5 Estimate tenths from grid line to point.
6 If reporting beyond 10" in any direction, prefix Grid Zone Designation, as: 12TUVW203

GRID ZONE IDENTIFICATION

VA WA
VV WV

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS

1 Read letters identifying 100,000 meter square in which the point lies.
2 Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.
3 Estimate tenths from grid line to point.
4 Locate first HORIZONTAL grid line below point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.
5 Estimate tenths from grid line to point.
6 If reporting beyond 10" in any direction, prefix Grid Zone Designation, as: 12TUVW203

TOWNSHIP OR RANGE LINE

LAND GRANT BOUNDARY

SALT LAKE CITY, UTAH; WYOMING

1954
REVISED 1970

STOCK NO. V502XNK1211*03