CANYON CITY

EDITION 3

NL 11-10
SERIES V502



V502, EDITION 3

Prepared by the U.S. Army Topographic Command (BEPM), Washington, D.C. Compiled in 1956 by photogrammetric methods and from United States quadrangles, 1:62,500, 1940-53. Planimetry revised in part from aerial photographs taken 1953. Photographs field annotated 1955. Revised by the U.S. Geological Survey 1970.

Area covered by dashed light-blue pattern is subject to controlled inundation

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES
- Over 500,000 — LOS ANGELES
- 100,000 to 500,000 — OMAHA
- 25,000 to 100,000 — GALVESTON
- 5,000 to 25,000 — Laramie
- 1,000 to 5,000 — Grand Coulee
- Less than 1,000 — Sun Valley

RAILROADS
- Standard gauge
- Narrow gauge

BOUNDARIES
- International
- State
- County
- Park or reservation

Single track / Double or Multiple

- Landplane airport
- Landing area
- Seaplane airport
- Dry lake
- Woods-brushwood

ROADS
- Primary, all-weather, hard surface
- Secondary, all-weather, hard surface
- Light-duty, all-weather, hard or improved surface
- Fair or dry weather, unimproved surface
- Trail
- Interchange
- Route markers: Interstate, U.S., State

- Mine
- Landmark: School; Church; Other
- Spot elevation in feet
- Marsh or swamp
- Intermittent or dry stream
- Power line

Scale 1:250,000

5 0 5 10 15 20 Statute Miles

5 0 5 10 15 20 25 30 Kilometers

5 0 5 10 15 Nautical Miles

CONTOUR INTERVAL 200 FEET
WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

BLACK DOTTED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 11

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 19½° (350 MILS) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 19° (340 MILS) EASTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR WASHINGTON, D.C. 20242

LOCATION DIAGRAM



SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

TOWNSHIP OR RANGE LINE
LAND GRANT BOUNDARY

GRID ZONE DESIGNATION: 11T

100,000 M. SQUARE IDENTIFICATION

KV LV MV
KU LU MU
490 30 40

IGNORE the SMALLER figures of any grid number; these are for finding the full coordinates. Use ONLY the LARGER figures of the grid number, example: 480000

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS

SAMPLE POINT: JOAQUIN MILLER RESORT

1. Read letters identifying 100,000 meter square in which the point lies: LV
2. Locate fyd VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself: 4
Estimate tenths from grid line to point: 3
3. Locate fyd HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself: 0
Estimate tenths from grid line to point: 5

SAMPLE REFERENCE: LV4305

If reporting beyond 18° in any direction, prefix Grid Zone Designation, as: 11TLV4305

CANYON CITY, OREGON
1955
REVISED 1970

STOCK NO. V502XNL11110**03

USGS HISTORIC TOPOGRAPHY
DMA 6000
JAN 12

● INTERIOR—GEOLOGICAL SURVEY, WASHINGTON, D. C.—1972