



Prepared by the U.S. Army Topographic Command (HYSG), Washington, D.C. Compiled in 1957 by photogrammetric methods and from United States quadrangles 1:50,000 and 1:62,500, 1948-57. Planimetry revised from aerial photographs taken 1956. Photographs field annotated 1957. Revised in 1971 by the U.S. Geological Survey from aerial photographs taken 1971.

Transverse Mercator Projection. 10,000-meter Universal Transverse Mercator grid, zone 11. 100,000-foot grid based on Nevada coordinate system west zone, 1927 North American Datum. To place on the predicted North American Datum 1983 move the projection lines 13 meters north and 85 meters east.

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram.

There may be private inholding within the boundaries of the National or State reservations shown on this map.

USGS
science for a changing world

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES

Over 500,000
100,000 to 500,000
25,000 to 100,000
5,000 to 25,000
1,000 to 5,000
Less than 1,000

ROADS

Primary, all-weather, hard surface
Secondary, all-weather, hard surface
Light-duty, all-weather, hard or improved surface
Fair or dry weather, unimproved surface
Trail
Interchange

RAILROADS

Normal gauge
Narrow gauge
Landplane airport
Seaplane airport
Dry lake
Woods-brushwood

BOUNDARIES

International
State
County
Park or reservation

Other Symbols

Windmill; Mine
Landmark: School, Church, Other
Spot elevation in feet
Marsh or swamp
Intermittent or dry stream
Power line

Scale 1:250,000

0 5 10 15 20 25 30 Statute Miles

0 5 10 15 20 25 30 Kilometers

0 5 10 15 20 25 30 Nautical Miles

CONTOUR INTERVAL 200 FEET

WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 17° (310 MILS) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 17° (300 MILS) EASTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, P.O. BOX 25286, DENVER, COLORADO 80225

A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

LOCATION DIAGRAM

NK 108	NK 109	NK 110	NK 111	NK 112	NK 113
NEVADA	NEVADA	NEVADA	NEVADA	NEVADA	NEVADA
NK 101	NK 102	NK 103	NK 104	NK 105	NK 106
NEVADA	NEVADA	NEVADA	NEVADA	NEVADA	NEVADA
NK 107	NK 108	NK 109	NK 110	NK 111	NK 112
NEVADA	NEVADA	NEVADA	NEVADA	NEVADA	NEVADA
NK 113	NK 114	NK 115	NK 116	NK 117	NK 118
NEVADA	NEVADA	NEVADA	NEVADA	NEVADA	NEVADA

SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

GRID ZONE DESIGNATION

18 15

TO GIVE A STANDARD REFERENCE ON TWO SHEETS TO NEAREST 100 METERS

SAMPLE POINT - GRID

KQ	LQ	MQ
KP	LP	MP

TO GIVE A STANDARD REFERENCE ON TWO SHEETS TO NEAREST 100 METERS

1. Read letters identifying 100,000 meter square in which the point lies.
2. Locate first VERTICAL grid line to left of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.
3. Locate first HORIZONTAL grid line to point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.
4. Estimate tenths from grid line to point.
If reporting beyond 10" in any direction, prefix Grid Zone Designation, as:

SAMPLE REFERENCE

4330000

11SP24

RECEIVED
SEP 30 2000
USGS NW0
HISTORICAL MAP ARCHIVES

