



Prepared by the Army Map Service (ASTT), Corps of Engineers, U.S. Army, Washington, D.C. Compiled in 1955 by photogrammetric methods and from South Dakota 1:24,000 and 1:25,000, USGS, 1898-1954. Planimetric detail by photo-planimetric methods. Horizontal and vertical control by USGS, USC&GS and USGS. Photography field annotated 1955. Limited revision by U.S. Geological Survey 1964. 100,000-foot grid based on South Dakota coordinate system, south zone 10,000-meter Universal Transverse Mercator grid ticks, zone 13, shown in blue.

**LEGEND**

**ROAD DATA 1955** PARTIALLY REVISED 1964  
Figures in red denote approximate distances in miles between stars

**POPULATED PLACES**

- Over 500,000
- 100,000 to 500,000
- 25,000 to 100,000
- 5,000 to 25,000
- 1,000 to 5,000
- Less than 1,000

**RAILROADS**

- Standard gauge
- Narrow gauge
- Interstate
- State
- County
- Park or reservation

**Landmarks: School; Church; Other**

- Horizontal control point
- Spot elevation in feet
- Marsh or swamp
- Intermittent or dry stream
- Power line

**BOUNDARIES**

- International
- State
- County
- Park or reservation

**Approximate road alignment**

Scale 1:250,000

5 10 15 20 25 30 Statute Miles

5 10 15 20 25 30 Kilometers

5 10 15 20 25 30 Nautical Miles

CONTOUR INTERVAL 200 FEET  
WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS  
TRANSVERSE MERCATOR PROJECTION

1960 MAGNETIC DECLINATION FOR THIS SHEET VARIES FROM 13°45' EASTERLY FOR THE CENTER OF THE WEST EDGE TO 12°30' EASTERLY FOR THE CENTER OF THE EAST EDGE. MEAN ANNUAL CHANGE IS 0°02' WESTERLY.

FOR SALE BY U. S. GEOLOGICAL SURVEY, DENVER 25, COLORADO OR WASHINGTON 25, D. C.

LOCATION DIAGRAM FOR NK 13-3

RELIABILITY DIAGRAM

USGS HISTORICAL FILE TOPOGRAPHIC DIVISION

SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

AUG 4 1964

3400

HOT SPRINGS, SOUTH DAKOTA; NEBRASKA

1955 LIMITED REVISION 1964