V501, EDITION 3

Prepared by the U.S. Army Topographic Command (KCSX), Washington, D.C. Compiled in 1956 by photogrammetric methods and from United States quadrangles, 1:25,000, 1947-53; USC & GS charts 1246, 1955; 1247, 1954. Planimetry revised in part from aerial photographs taken 1950-51. Revised in 1972 by the U.S. Geological Survey from aerial photographs taken 1969-1972.

Selected hydrographic data compiled from USC&GS charts 1954-1955. This information is not intended for navigational purposes

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES
- Over 500,000 — BOSTON
- 100,000 to 500,000 — RICHMOND
- 25,000 to 100,000 — EVANSTON
- 5,000 to 25,000 — Hialeah
- 1,000 to 5,000 — Bar Harbor
- Less than 1,000 — Fishkill

RAILROADS (Single track, Double or Multiple)
- Standard gauge
- Narrow gauge

BOUNDARIES
- International
- State
- County
- Park or reservation

Spot elevation in feet — 22′

ROADS
- Primary, all-weather, hard surface
- Secondary, all-weather, hard surface
- Light-duty, all-weather, hard or improved surface
- Fair or dry weather, unimproved surface
- Trail
- Interchange

Route markers: Interstate, U.S., State

- Landmark: School; Church; Other
- Landplane airport
- Depth curve in feet
- Landing area
- Limit of danger; Reef
- Seaplane airport
- Rocks; Awash
- Power line
- Foreshore flat; Mangrove
- Orchard
- Intermittent or dry stream
- Woods-brushwood
- Marsh or swamp

Scale 1:250,000

5 0 5 10 15 20 Statute Miles

5 0 5 10 15 20 25 30 Kilometers

5 0 5 10 15 Nautical Miles

CONTOUR INTERVAL 50 FEET
WITH SUPPLEMENTARY CONTOURS AT 25 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 17

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM ½° (10 MILS) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 1° (20 MILS) WESTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U. S. GEOLOGICAL SURVEY, RESTON VIRGINIA 22092

LOCATION DIAGRAM



GRID ZONE DESIGNATION 17 R	TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1,000 METERS
100,000 M. SQUARE IDENTIFICATION: MA / NA / MV / NV	SAMPLE POINT: BRIGHTON 1. Read letters identifying 100,000 meter square in which the point lies: MA 2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself. 9 Estimate tenths from grid line to point: 1 3. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself. 1 Estimate tenths from grid line to point: 1
IGNORE the SMALLER figures of any grid number; these are for finding the full coordinates. Use ONLY the LARGER figure of the grid number, example: 2990000 m.	SAMPLE REFERENCE: MA9111 If reporting beyond 18° in any direction, prefix Grid Zone Designation, as: 17MA9111

USGS
Historical File
Topographic Division

DEC 16 197
DEC 16 197

FORT PIERCE, FLORIDA
1956
REVISED 1972

STOCK NO. V501XNG172***03

● INTERIOR—GEOLOGICAL SURVEY, RESTON, VIRGINIA—1974