




CONVERSION
SCALES





Feet	Meters
1	3048
2	6096
3	9144
4	12192
5	15240
6	18288
7	21286
8	24284
9	27282
10	30280

To convert feet to meters
multiply by 3048
To convert meters to feet
multiply by 3.2808

1. Dryland
2. Wetlands (May be partially submerged at mean high tide)
3. Exposed at mean low tide



Produced by the United States Geological Survey and National Ocean Survey
Control by the USGS and NOS/NOAA
Orthophotomap prepared from aerial photograph taken January 18, 1976. Compiled by photogrammetric methods from aerial photographs taken January 1975 and planetable surveys 1978. Field checked 1978. Map edited 1982. Supersedes topographic map dated 1956.
Bathymetry compiled by the National Ocean Survey from tide-coordinated hydrographic surveys.
This information is not intended for navigational purposes.
Mean low water (dotted) line and mean high water (solid) line compiled by NOS from tide-coordinated aerial photographs. Apparent shoreline (outer edge of vegetation) shown by photogrammetry.
Projection and 10,000-foot grid ticks: Florida coordinate system, north zone (Lambert conformal conic).
1000-meter Universal Transverse Mercator grid, zone 16 1927 North American Datum.
To place on the predicted North American Datum 1983 move the projection lines 20 meters south and 7 meters west as shown by dashed corner ticks.
There may be private inholdings within the boundaries of the National or State reservations shown on this map.



Survey Number	Survey Date	Survey Scale	Survey Line spacing (Naut. Miles)
H-12654	1975	1:20,000	10-90
H-13746	1977	1:20,000	03-80
H-15115	1982	1:40,000	15-80
H-7631	1947	1:40,000	15-20
H-7632	1947	1:40,000	05-26
H-9734	1977	1:20,000	03-11

SCALE 1:24 000
CONTOUR INTERVAL 2 METERS
SUPPLEMENTARY CONTOUR INTERVAL 1 METER
NATIONAL GEODETIC VERTICAL DATUM OF 1929
CONTROL ELEVATIONS SHOWN TO THE NEAREST 0.1 METER
OTHER ELEVATIONS SHOWN TO THE NEAREST 0.5 METER
BATHYMETRIC CONTOUR INTERVAL 1 METER WITH SUPPLEMENTARY 0.5 METER CONTOURS—DATUM IS MEAN LOWER LOW WATER
THE RELATIONSHIP BETWEEN THE TWO DATUMS IS VARIABLE
THE MEAN RANGE OF TIDE IS APPROXIMATELY 0.4 METER
BASE MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS ORGANIZATION (IHO) SPECIAL PUBLICATION 44 ACCURACY STANDARDS AND/OR STANDARDS USED AT THE DATE OF THE SURVEY
FOR SALE BY U. S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092 AND NATIONAL OCEAN SURVEY, ROCKVILLE, MARYLAND 20852
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST



ROAD CLASSIFICATION
Primary highway, hard surface
Secondary highway, hard surface
Trails
Interstate Route
U. S. Route
County Route
Light-duty road, hard or improved surface
Unimproved road
State Route

CROOKED ISLAND, FLA.
29085-H5-TB-024
1982
DMA 3843 1 NE—SERIES V8470